

SPECIFICATIONS



2013 Ram 1500 SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION

Vehicle Type	Regular Cab, Quad Cab, and Crew Cab, 2WD, 4WD
Assembly Plant	Regular Cab: Saltillo Truck Assembly, Saltillo, Mexico Quad Cab: Warren Truck Assembly Plant, Warren, Mich. Crew Cab: Warren Truck Assembly Plant, Warren, Mich.
EPA Vehicle Class	Standard Pickup

BODY/CHASSIS

Layout	2WD — Longitudinal, front engine 4WD — Longitudinal, front engine, transfer case
Construction	2WD — Ladder-type frame, steel cab, double-wall steel pickup box 4WD — Ladder-type frame, steel cab, double-wall steel pickup box

ENGINE: 3.6-LITER 24-VALVE DOHC V-6 E85

Type and Description	60-degree V-type, liquid-cooled
Displacement	220 cu. in. (3604 cu. cm)
Bore x Stroke	3.78 x 3.27 (96.0 x 83.0)
Valve System	Chain-driven DOHC, 24 valves and hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	10.2:1
Power (SAE net)	305 hp (224 kW) at 6,400 rpm
Torque (SAE net)	269 lb.-ft. (364 N•m) at 4,175 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2, E85-compatible
Oil Capacity	6.0 qt. (5.7 liter)
Coolant Capacity	14.0 qt. (13.25 liter)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors
Estimated EPA Fuel Economy mpg (city/hwy)	TBA

SPECIFICATIONS



ENGINE: 4.7-LITER SOHC 16-VALVE SMPI V-8 E85

Type and Description	90-degree V-8, liquid-cooled
Displacement	287 cu. in. (4701 cu. cm)
Bore x Stroke	3.66 x 3.40 (93.0 x 86.5)
Valve System	Chain-driven SOHC, 16 valves
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	9.0:1
Power (SAE net)	310 hp (231 kW) @ 5,650 rpm
Torque (SAE net)	330 lb.-ft. (447 N•m) @ 3,950 rpm
Max. Engine Speed	6,000 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2, E85-compatible
Oil Capacity	6.0 qt. (5.7 liter)
Coolant Capacity	10.8 qt. (10.23 liter)
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features
Estimated EPA Fuel Economy mpg (city/hwy)	TBA

ENGINE: 5.7-LITER HEMI® 16-VALVE V-8

Type and Description	90-degree V-8, liquid-cooled
Displacement	345 cu. in. (5654 cu. cm)
Bore x Stroke	3.92 x 3.58 (99.5 x 90.9)
Valve System	Variable cam timing, pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
Power (SAE net)	395 hp (291 kW) @ 5,600 rpm
Torque (SAE net)	407 lb.-ft. (548 N•m) @ 3,950 rpm
Max. Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — recommended Unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	7.0 qt. (6.6 liter)
Coolant Capacity	14.0 qt. (13.33 liter)
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features
Estimated EPA Fuel Economy mpg (city/hwy) 8-speed automatic	TBA
Estimated EPA Fuel Economy mpg (city/hwy) 6-speed automatic	TBA

SPECIFICATIONS



TRANSMISSION: 65RFE AUTOMATIC SIX-SPEED

Availability	Standard with 4.7-liter V-8, available with 5.7-liter V-8 equipped trucks
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios	
1st	3.00
2nd	1.67
3rd	1.50
4th	1.00
5th	0.75
6th	0.67
Reverse	3.00
Final Drive and Overall Top Gear Ratios	2.15 with 3.21 axle; 2.38 with 3.55 axle; 2.63 with 3.92 axle; and 2.75 with 4.10 axle
Max Torque	410 lb.-ft. (540 N•m)

TRANSMISSION: ZF 8HP45 AUTOMATIC EIGHT-SPEED WITH ELECTRONIC RANGE SELECT (ERS)

Availability	Standard with 3.6-liter V-6 equipped trucks
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Final Drive and Overall Top Gear Ratios	2.15 with 3.21 axle; 2.38 with 3.55 axle
Max Torque	332 lb.-ft. (450 N•m)

SPECIFICATIONS



TRANSMISSION: ZF 8HP70 AUTOMATIC EIGHT-SPEED WITH ELECTRONIC RANGE SELECT (ERS)

Availability	Available with select 5.7-liter V-8 equipped trucks
Description	Adaptive electronic control, automatic or ERS manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Final Drive and Overall Top Gear Ratios	2.15 with 3.21 axle; 2.38 with 3.55 axle; 2.63 with 3.92 axle
Max Torque	516 lb.-ft. (700 N•m)

TRANSFER CASE: BW 44-45 PART-TIME

Availability	3.6-liter V-6 4x4, 4.7-liter V-8 4x4 and 5.7-liter V-8 4x4
Shift Mechanism	Electric
Available Speeds	2-speed
Operating Modes	2WD High; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Center Differential Type	None

TRANSFER CASE: BW 44-44 ON-DEMAND

Availability	5.7-liter V-8 4x4
Shift Mechanism	Electric
Available Speeds	2-speed
Operating Modes	2WD High; 4WD Auto; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Center Differential Type	None

AXLES

Front	ZF 215 mm
Rear	C235 mm (available limited slip)
Available Ratios	3.21, 3.55, 3.92, 4.10

SPECIFICATIONS



ELECTRICAL SYSTEM

Architecture	Powernet
Alternator	160-amp, 180-amp, 220-amp (Stop-start only)
Battery	Group 65, low-maintenance 730 CCA (Stop-start features 800 CCA Absorbed Glass Mat)

SUSPENSION

Front	Upper and lower "A" arms, coil springs, twin-tube shock absorbers, stabilizer bar. Optional air suspension replaces twin-tube shock absorbers and coil springs
Rear	Five-link with track bar, coil springs, stabilizer bar, twin-tube shock absorbers, solid axle. Optional air suspension replaces twin-tube shock absorbers and coil springs

STEERING

Power-assist	Electric power steering
--------------	-------------------------

Regular Cab	2WD	2WD	4WD	4WD
Box Length	Short Box (6 ft. 4 in.)	Long Box (8 ft.)	Short Box (6 ft. 4 in.)	Long Box (8 ft.)
Wheelbase (nominal)	120.5 (3061)	140.5 (3569.2)	140.5 (3569.2)	140.5 (3569.2)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire -ft. (m)(a)	39.5 (12.0)	45.1 (13.7)	39.8 (12.1)	45.4 (13.8)
Turning Diameter – 20-in. Tire - ft. (m)(a)	39.3 (12.0)	44.9 (13.7)	39.8 (12.1)	45.5 (13.9)
Turning Diameter – 17-in. Outdoorsman Tire – ft. (m)(a)	N/A	N/A	39.4 (12.0)	45.0 (13.7)

Quad Cab	2WD	4WD
Box Length	Long Box (6 ft. 4 in.)	Long Box (6 ft. 4 in.)
Wheelbase (nominal)	140.5 (3569.2)	140.5 (3569.2)
Overall Steering Ratio	17.9:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter – 17-in. Tire -ft. (m)(a)	45.1 (13.7)	45.4 (13.8)
Turning Diameter – 20-in. Tire - ft. (m)(a)	44.9 (13.7)	45.5 (13.9)
Turning Diameter – 17-in. Outdoorsman Tire – ft. (m)(a)	44.8 (13.7)	45.0 (13.7)

SPECIFICATIONS



Crew Cab	2WD	2WD	4WD	4WD
Box Length	Short Box (5 ft. 7 in.)	Long Box (6 ft. 4 in.)	Short Box (5 ft. 7 in.)	Long Box (6 ft. 4 in.)
Wheelbase (nominal)	140.5 (3061)	149.5 (3569.2)	140.5 (3569.2)	149.5 (3569.2)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire -ft. (m)(a)	39.5 (12.0)	45.1 (13.7)	39.8 (12.1)	45.4 (13.8)
Turning Diameter – 20-in. Tire - ft. (m)(a)	39.3 (12.0)	44.9 (13.7)	39.8 (12.1)	45.5 (13.9)
Turning Diameter – 17-in. Outdoorsman Tire – ft. (m)(a)	N/A	N/A	39.4 (12.0)	45.0 (13.7)

CHASSIS

Layout	Longitudinal, front engine (optional transfer case)
Construction	Ladder-type frame, steel cab, double-wall steel pickup box

BRAKES

Front	Size and Type 13.2 x 1.1 (336 x 28) vented disc with 2.13 (54) two-piston pin-slider caliper and ABS Swept Area 292 sq. in. (1884 sq. cm)
Rear	Size and Type 13.8 x 0.87 (352 x 22) disc with 2.13 (54) single-piston pin-slider caliper and ABS Swept Area 274 sq. in. (1768 sq. cm)
Power-assist	Dual-rate, tandem diaphragm vacuum

SPECIFICATIONS



DIMENSIONS AND CAPACITIES

Regular Cab Pickup

<i>Model – Tire Size</i>	<i>2WD –265/70R17</i>		<i>4WD –265/70R17</i>	
Box Length	6ft. 4in.	8ft.	6ft. 4in.	8ft.
Wheelbase (nominal)	120.5 (3061.2)	140.5 (3569.2)	120.5 (3062.5)	140.5 (3570.2)
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.2 (1732.3)	68.2 (1732.3)
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)
Overall Length	209.0 (5308.5)	231.0 (5866.5)	209.0 (5308.5)	231.0 (5866.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	74.6 (1894.2)	74.4 (1889.2)	75.2 (1910.4)	75.0 (1906.2)
Ground Clearance				
Front Axle	9.0 (229.3)	9.0 (229.2)	9.2 (232.6)	9.2 (232.7)
Rear Axle	8.7 (221.2)	8.7 (221.5)	8.6 (219.2)	8.6 (219.5)
Open Tailgate to Ground	34.8 (883.4)	34.6 (878.3)	35.0 (889.6)	34.9 (885.3)
Pickup Body Height	20.1 (511.1)	20.2 (513.0)	20.1 (511.1)	20.2 (513.0)
Approach Angle (degrees)	15.6	15.7	17.7	17.8
Departure Angle (degrees)	25.2	24.1	25.6	24.4
Ramp Breakover Angle (degrees)	21.5	19.2	22.9	20.5
Fuel-Tank Capacity	26-gal. (98-liter) (Standard)	32-gal. (121-liter) (Standard)	26-gal. (98-liter) (Standard)	32-gal. (121-liter) (Standard)

Quad Cab 6-ft. 4-in. Box Pickup

<i>Model – Tire Size</i>	<i>2WD –265/70R17</i>		<i>4WD –265/70R17</i>	
Wheelbase (nominal)	140.5 (3569.2)		140.5 (3570.2)	
Track, Front	68.0 (1728.2)		68.2 (1732.3)	
Track, Rear	67.5 (1714.7)		67.5 (1714.7)	
Overall Length	229.0 (5816.5)		229.0 (5816.5)	
Overall Width	79.4 (2017.4)		79.4 (2017.4)	
Overall Height	77.2 (1960.2)		77.7 (1974.8)	
Ground Clearance				
Front Axle	9.0 (229.2)		9.2 (232.7)	
Rear Axle	8.7 (221.5)		8.6 (219.5)	
Open tailgate to ground	34.6 (878.3)		34.9 (885.3)	
Pickup Body Height	20.1 (511.1)		20.1 (511.1)	
Approach Angle (degrees)	15.7		17.8	
Departure Angle (degrees)	25.1		25.4	
Ramp Breakover Angle (degrees)	19.2		20.5	
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)		26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	

SPECIFICATIONS



Quad Cab 6ft. 4in. Box Pickup – Outdoorsman

Model – Tire Size	2WD –275/60R20	4WD –275/60R20
Wheelbase (nominal)	140.5 (3569.4)	140.7 (3573.5)
Track, Front	68.6 (1742.2)	68.6 (1743.2)
Track, Rear	68.0 (1727.4)	68.0 (1727.4)
Overall Length	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)
Overall Height	77.9 (1979.4)	78.8 (2001.6)
Ground Clearance		
Front Axle	9.6 (244.8)	9.8 (248.6)
Rear Axle	9.3 (237.0)	9.2 (233.2)
Open tailgate to ground	(887.7)	(903.5)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	21.3	23.9
Departure Angle, (degrees)	21.4	22.1
Ramp Breakover Angle (degrees)	20.9	18.8
Ground Clearance without Skid Plate	10.3 (261.5)	NA
Ground Clearance with Skid Plate	NA	9.9 (252.2)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	75.2 (1909.0)	77.2 (1962.0)	78.2 (1986.6)	79.2 (2013.0)
Ground Clearance				
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

Suspension Mode	Tire Size 275/60R20			
	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)
Track, Front	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)
Track, Rear	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	75.8 (1924.4)	77.8 (1977.4)	78.8 (2002.0)	79.9 (2028.4)
Ground Clearance				
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	75.2 (1909.0)	77.2 (1962.0)	78.2 (1986.6)	79.2 (2013.0)
Ground Clearance				
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	15.2	19.7	21.8	22.9
Departure Angle (degrees)	18.7	20.6	21.4	22.9
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0
Ramp Breakover Angle, with Skid Plate	12.7	15.9	17.6	19.2
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)
Track, Front	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)
Track, Rear	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	75.8 (1924.4)	77.8 (1977.4)	78.8 (2002.0)	79.9 (2028.4)
Ground Clearance				
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.2	23.6
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Crew Cab Pickup

<i>Model – Tire Size</i>	<i>2WD –265/70R17</i>		<i>4WD –265/70R17</i>	
Box Length	<i>5ft. 7in.</i>	<i>6ft. 4in.</i>	<i>5ft. 7in.</i>	<i>6ft. 4in.</i>
Wheelbase (nominal)	140.5 (3569.2)	149.4 (3795.3)	140.5 (3570.2)	149.4 (3795.2)
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.2 (1732.3)	68.2 (1732.3)
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)
Overall Length	229.0 (5816.5)	237.9 (6042.6)	229.0 (5816.5)	237.9 (6042.6)
Overall Width	79.4 (2017.4)	79.4 (2016.6)	79.4 (2017.4)	79.4 (2016.6)
Overall Height	76.9 (1953.8)	76.8 (1950.6)	77.5 (1967.9)	77.4 (1965.1)
Ground Clearance				
Front Axle	9.0 (229.2)	9.1 (231.1)	9.2 (232.7)	9.2 (235.2)
Rear Axle	8.7 (221.5)	8.7 (220.5)	8.6 (219.5)	8.6 (218.3)
Open Tailgate to Ground	34.6 (878.3)	34.4 (874.0)	34.9 (885.3)	34.7 (880.8)
Pickup Body Height	20.0 (508.6)	20.1 (511.1)	20.0 (508.6)	20.1 (511.1)
Approach Angle (degrees)	15.7	16.0	17.8	18.0
Departure Angle (degrees)	25.1	24.9	24.7	25.2
Ramp Breakover Angle (degrees)	19.2	18.5	20.5	19.7
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Crew Cab Pickup - Outdoorsman

<i>Model – Tire Size</i>	<i>2WD –275/60R20</i>		<i>4WD –275/60R20</i>	
Box Length	<i>5ft. 7in.</i>	<i>6ft. 4in.</i>	<i>5ft. 7in.</i>	<i>6ft. 4in.</i>
Wheelbase (nominal)	140.5 (3569.4)	149.4 (3795.8)	140.7 (3573.5)	149.6 (3799.6)
Track, Front	68.6 (1742.2)	68.6 (1742.2)	68.6 (1743.2)	68.6 (1743.2)
Track, Rear	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)
Overall Length	229.0 (5816.5)	237.9 (6042.6)	229.0 (5816.5)	237.9 (6042.6)
Overall Width	79.4 (2017.4)	79.4 (2016.6)	79.4 (2017.4)	79.4 (2016.6)
Overall Height	77.6 (1972.3)	77.5 (1968.1)	78.5 (1994.1)	78.4 (1991.7)
Ground Clearance				
Front Axle	9.6 (244.8)	9.6 (243.6)	9.8 (248.6)	9.8 (248.0)
Rear Axle	9.3 (237.0)	9.3 (235.0)	9.2 (233.2)	9.2 (233.1)
Open Tailgate to Ground	34.9 (887.7)	34.8 (883.9)	35.6 (903.5)	35.5 (902.3)
Pickup Body Height	20.0 (508.6)	20.1 (511.1)	20.0 (508.6)	20.1 (511.1)
Approach Angle (degrees)	21.3	21.0	23.9	22.9
Departure Angle (degrees)	21.4	21.2	22.1	22.1
Ramp Breakover Angle (degrees)	20.9	19.9	18.8	17.6
Ground Clearance without Skid Plate	10.3 (261.5)	10.3 (261.0)	NA	NA
Ground Clearance with Skid Plate	NA	NA	9.9 (252.2)	9.9 (251.6)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>		<i>265/70R17</i>		
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	74.9 (1902.1)	77.0 (1955.1)	77.9 (1979.2)	79.0 (2006.1)
Ground Clearance				
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>		<i>275/60R20</i>		
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)
Track, Front	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)
Track, Rear	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	75.5 (1917.4)	77.6 (1970.4)	78.5 (1994.5)	79.6 (2021.4)
Ground Clearance				
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)

SPECIFICATIONS



Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

Tire Size	265/70R17			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	74.9 (1902.1)	77.0 (1955.1)	77.9 (1979.2)	79.0 (2006.1)
Ground Clearance				
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	15.2	19.7	21.8	22.9
Departure Angle (degrees)	18.7	20.6	21.4	22.9
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0
Ramp Breakover Angle with Skid Plate	12.7	15.9	17.6	19.2
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>		<i>275/60R20</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2	
Wheelbase (nominal)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	140.5 (3569.4)	
Track, Front	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)	
Track, Rear	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	
Overall Length	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	229.0 (5816.5)	
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	
Overall Height	75.5 (1917.4)	77.6 (1970.4)	78.5 (1994.5)	79.6 (2021.4)	
Ground Clearance					
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)	
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	
Approach Angle (degrees)	16.6	20.9	22.9	24.0	
Departure Angle (degrees)	19.4	21.3	22.2	23.6	
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2	
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3	
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)	
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)	
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>		<i>265/70R17</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2	
Wheelbase (nominal)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)	
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)	
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	
Overall Length	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)	
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	
Overall Height	74.7 (1897.7)	76.8 (1950.7)	77.8 (1975.2)	78.8 (2001.7)	
Ground Clearance					
Front Axle	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)	
Rear Axle	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)	

SPECIFICATIONS



Open Tailgate to Ground	32.6 (827.9)	34.1 (866.6)	34.8 (885.2)	36.1 (917.6)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	22.8	24.6	25.5	26.9
Ramp Breakover Angle (degrees)	15.3	18.7	20.5	22.2
Ground Clearance without Skid Plate	6.7 (170.0)	8.8 (222.7)	9.9 (252.4)	10.8 (273.7)
Ground Clearance with Skid Plate	6.0 (152.3)	8.1 (205.4)	9.3 (235.4)	10.1 (256.4)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

Tire Size

275/60R20

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)
Track, Front	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)
Track, Rear	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)
Overall Length	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	75.4 (1914.5)	77.5 (1967.5)	78.4 (1991.9)	79.5 (2018.5)
Ground Clearance				
Front Axle	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)
Rear Axle	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)
Open Tailgate to Ground	32.3 (819.5)	34.8 (883.9)	35.5 (902.5)	36.8 (934.9)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	15.5	19.7	22.3	23.9
Departure Angle (degrees)	22.5	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	16.4	19.8	21.7	23.3
Ground Clearance without Skid Plate	7.3 (185.8)	9.4 (239.0)	10.6 (268.7)	11.4 (290.0)
Ground Clearance with Skid Plate	6.6 (168.8)	8.7 (221.7)	9.9 (251.7)	10.7 (272.7)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)
Track, Front	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)	68.0 (1728.2)
Track, Rear	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)	67.5 (1714.7)
Overall Length	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	74.7 (1897.7)	76.8 (1950.7)	77.8 (1975.2)	78.8 (2001.7)
Ground Clearance				
Front Axle	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)
Rear Axle	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)
Open Tailgate to Ground	32.6 (827.9)	34.1 (866.6)	34.8 (885.2)	36.1 (917.6)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	15.3	19.7	21.8	22.9
Departure Angle (degrees)	18.6	20.4	21.3	22.7
Ramp Breakover Angle without Skid Plate	15.3	18.7	20.5	22.2
Ramp Breakover Angle with Skid Plate	12.0	15.0	16.6	18.2
Ground Clearance without Skid Plate	6.7 (170.0)	8.8 (222.7)	9.9 (252.4)	10.8 (273.7)
Ground Clearance with Skid Plate	6.0 (152.3)	8.1 (205.4)	9.3 (235.4)	10.1 (256.4)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

SPECIFICATIONS



Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

Tire Size	275/60R20			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)	149.5 (3798.0)
Track, Front	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)	68.6 (1742.2)
Track, Rear	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)	68.0 (1727.4)
Overall Length	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)	237.9 (6042.6)
Overall Width	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height	75.4 (1914.5)	77.5 (1967.5)	78.4 (1991.9)	79.5 (2018.5)
Ground Clearance				
Front Axle	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)
Rear Axle	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)
Open Tailgate to Ground	32.3 (819.5)	34.8 (883.9)	35.5 (902.5)	36.8 (934.9)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.1	23.6
Ramp Breakover Angle without Skid Plate	16.4	19.8	21.7	23.3
Ramp Breakover Angle with Skid Plate	13.0	16.0	17.7	19.2
Ground Clearance without Skid Plate	7.3 (185.8)	9.4 (239.0)	10.6 (268.7)	11.4 (290.0)
Ground Clearance with Skid Plate	6.6 (168.8)	8.7 (221.7)	9.9 (251.7)	10.7 (272.7)
Fuel-Tank Capacity	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)	26-gal. (98-liter) (Standard) 32-gal. (121-liter) (Optional)

Cargo Box

Nominal Box Size	5 ft 7 in (Crew)	6 ft 4 in (Regular, Quad, or Crew)	8 ft (Regular)
SAE volume, cu. ft. (cu m)	50.3 (1.4)	57.5 (1.6)	74.7 (2.1)
Length at Floor, Tailgate Closed	67.4 (1712.4)	76.3 (1938.5)	98.3 (2496.5)
Cargo Width	66.4 (1686.9)	66.4 (1686.9)	66.4 (1686.9)
Distance Between Wheelhouses	51 (1295.4)	51 (1295.4)	51 (1295.4)
Depth	20.0 (508.6)	20.1 (511.1)	20.2 (513.0)
Tailgate Opening Width in. – (mm)	60.4 (1535.3)	60.4 (1535.3)	60.4 (1535.3)

SPECIFICATIONS



ACCOMMODATIONS

Model	Regular Cab	Quad Cab	Crew Cab
Seating Capacity, F/R	3/0 or 2/0	3/3 or 2/3	3/3 or 2/3
Front			
Head Room	39.9 (1013.5)	41.0 (1041.4)	41.0 (1041.4)
Legroom	41.0 (1041.4)	41.0 (1041.4)	41.0 (1041.4)
Shoulder Room	66.0 (1676.4)	66.0 (1676.4)	66.0 (1676.4)
Hip Room	62.9 (1598.7)	63.2 (1605.3)	63.2 (1605.3)
Seat Travel	9.0 (230.0)	9.0 (230.0)	9.0 (230.0)
Recliner Range (degrees)	85 (38 Rwd, 47 Fwd)	56 (38 Rwd, 18 Fwd)	56 (38 Rwd, 18 Fwd)
Rear			
Head Room	N/A	39.7 (1008.4)	39.9 (1013.5)
Legroom	N/A	34.7 (880.9)	40.3 (1023.3)
Shoulder Room	N/A	65.7 (1668.8)	65.7 (1668.8)
Hip Room	N/A	62.9 (1598.3)	63.2 (1605.3)
Interior Volume			
Front – cu. ft. (cu m)	62.5 (1.8)	64.2 (1.8)	64.2 (1.8)
Rear – cu. ft. (cu m)	N/A	52.4 (1.5)	61.1 (1.7)

* * *