

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

2007 Dodge Caliber SRT4 FEATURE AVAILABILITY

EXTERIOR

Colors: Brilliant Black, Sunburst Orange, Bright Silver, Inferno Red _____	O
Fascia	
Front—all new with functional brake and radiator cooling ducts _____	S
Rear—lower vertical strakes to direct underbody airflow _____	S
Fascia/Grille—designed for aggressive SRT-signature look _____	S
Hood—with functional air scoop and exhaust extractors _____	S
Lamps	
Halogen headlamps _____	S
Fog lamps _____	S
Mirrors	
Power _____	S
Rear spoiler—large, integrated _____	S
Rear window defroster _____	S
Sun roof power express open/close _____	S
Windows	
Solar control glass _____	S
Power windows, driver one-touch _____	S
Wiper system	
Windshield, variable, intermittent _____	S
Rear window wiper/washer _____	S

INTERIOR

Air conditioning _____	S
Interior colors: Dark/Light Slate Gray _____	S
Décor—SRT race-inspired graphic design, including instruments, separate turbocharger boost gauge and silver finish on center stack and interior trim _____	S
Alloy Silver finish on instrument panel and shift bezel _____	S
Floor covering	
Carpet _____	S
Vinyl washable and removable load floor covering _____	S
Center stack-mounted shifter with leather-finished shift knob _____	S
Console	
Full-length floor _____	S
Illuminated cup holders _____	S
12V auxiliary power outlet _____	S
115V auxiliary power outlet _____	S
Sliding armrest with cell phone holder _____	S
Floor mats, front and rear _____	S
Instrument cluster	
Performance-oriented instrumentation in three gauge “tunnels” include tachometer, 200-mph speedometer, water temperature and fuel gauges _____	S
Lamps	
Front dome lamp _____	S
Cargo compartment lamp _____	S
Map/dome reading lamps _____	S

Removable/rechargeable lamp _____	S
Illuminated entry _____	S
Passenger assist handles _____	S
Mirrors	
Rearview day/night mirror _____	S
Seats	
Sport seating with aggressive bolstering and performance fabric inserts	
Sound System	
AM/FM radio with multi-disc CD changer control _____	S
SIRIUS Satellite Radio	
SRT/Kicker high-performance audio system with 13 speakers, 322-watt amplifier and	
100-watt subwoofer _____	O
Speakers	
Four speakers _____	S
Speed control _____	S
Steering column, tilt _____	S
Steering wheel	
Leather-wrapped _____	S
Sun visors, sliding with mirrors _____	S
UConnect® Hands-free Communication System _____	O

POWERTRAIN AND CHASSIS

Turbocharged 2.4-liter I4 World engine _____	S
Siemens Global Powertrain Engine Controller _____	S
GF DMT-6 six-speed manual transmission _____	S
Brakes	
Heavy-duty four-wheel disc brakes with vented brake rotors _____	S
Differential—limited slip _____	S
ESP—uniquely calibrated _____	S
Exhaust—tuned with two catalytic converters _____	S
Steering	
Rack-and-pinion power steering tuned for easy low-speed maneuvering,	
uncompromising performance at speed _____	S
18.0:1 overall ratio _____	S
Suspension	
Upgraded MacPherson strut front suspension includes new suspension knuckles	
and tuned dampers with revised spring rates _____	S
Front and rear sway bars _____	S
Tires(a)	
225/45R19 W-rated Goodyear _____	S
Compact spare _____	S
Wheels	
SRT-unique 19-inch cast aluminum _____	S
Trailer Tow Group _____	O

(a) Another tire size or brand may also be used.

SAFETY AND SECURITY

Air bags	
Advanced multi-stage front air bags _____	S
Supplemental side window curtain _____	S
Inflatable knee-blocker—helps position driver relative to primary air bag _____	S
Anti-lock brakes (ABS)—four-wheel _____	S
Brake Assist _____	S
Brake/Park interlock _____	S
Energy-absorbing steering column _____	S
EARS _____	S
ESP _____	S
Interior head impact protection _____	S
Knee bolsters _____	S

HomeLink	S
Locks	
Manual locks	—
Speed sensitive power locks, includes liftgate	S
Lower Anchors and Tethers for Children (LATCH) child seat anchor system	S
Occupant Classification System (OCS)	S
ParkSense Rear Back-up System	S
Power adjustable brake, accelerator and clutch pedals	S
Remote keyless entry	S
Seat belts	
BeltAlert	S
Explain Acronym (CFR)	S
Height adjustable	S
Pretensioners	S
Sentry Key Engine Immobilizer	S
SmartBeam Headlamps	S
Sun roof—auto-reverse	S
TPM	S

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts.

Remember, a back seat is the safest place for children.

(b) Always sit properly in the seat with the seat belt fastened. Always observe the passenger air bag indicator lamp to determine if the OCS classification is appropriate. Children 12 and under should always be in a back seat correctly using an infant or child restraint system or the seat belt positioned correctly for the child's age and weight.

SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION

Body style	Five-door hatchback
Assembly Plant	Belvidere, Illinois
EPA Vehicle Class	Compact Car

ENGINE: 2.4-LITER DOHC 16-VALVE I4 WITH VARIABLE VALVE TIMING, TURBOCHARGED

Availability	Std.
Type and Description	Four cylinders in-line, tuned intake manifold with Electronic Active Charge Motion Control valves, dual counter-rotating balance shafts
Displacement	144 cu. in. (2360 cu. cm.)
Bore x Stroke	3.46 x 3.82 (88 x 97)
Valve System	Chain-driven DOHC, 16 valves, electronically controlled dual Variable Valve Timing, direct-acting shimless mechanical bucket tappets
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	High-pressure die cast aluminum block with dry iron liners, cast aluminum cylinder head, cast aluminum ladder frame, forged steel crankshaft
Compression	Ratio 8.6:1
Power (SAE net, estimated)	300 bhp (223 kW) @ 6,000 rpm (125 bhp/liter)
Torque (SAE net, estimated)	260 lb.-ft. (352 N•m) @ 2,000-6,000 rpm
Max. Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	Unleaded premium, 91 octane (R+M)/2
Oil Capacity	5.0 qt. (4.7L) SAE 0W/40 Mobil 1 Synthetic
Coolant Capacity	7.2 qt. (6.8L)
Emission Controls	Two catalytic converters, dual heated oxygen sensors and engine features
Max. Gross Trailer Weight	N/A
Estimated EPA Fuel Economy MPG City/Hwy	22/28

TRANSAXLE: MANUAL, GETRAG DMT-6 6-SPEED

Availability _____ Std.
Description _____ Six-speed, overdrive, synchronized in all ratios, cable-operated,
four-plane shifter with reverse lockout ring

Gear Ratios

1 st	3.231
2 nd	1.952
3 rd	1.321
4 th	0.971
5 th	1.061
6 th	0.886
Reverse	3.831
Final Drive Ratio	Gears 1-4: 4.063, gears 5,6: 2.955
Overall Top Gear	2.728

ELECTRICAL SYSTEM

Alternator _____ 140A
Battery _____ 700 CCA, maintenance-free

DIMENSIONS AND CAPACITIES

Wheelbase	103.7 (2635)
Track, Front	59.8 (1520)
Track, Rear	59.8 (1520)
Overall Length	173.8 (4413.9)
Overall Width	68.8 (1747.2)
Overall Height	60.4 (1533.1)
Ground Clearance	7.0 (178)
Frontal Area, sq. ft. (sq. m)	24.5 (2.28)
Drag Coefficient	0.4
Curb Weight, lb.—estimated (kg)	3189 (1447)
Weight Distribution, percent F/R	58/42

ACCOMMODATIONS

Seating Capacity, F/R	2/3
Front Head Room without sun roof	40.0 (1015.6)
Leg Room	41.8 (1061.5)
Shoulder Room	54.2 (1377.8)
Hip Room	52.2 (1325.3)
Seat Travel	Driver—10.2 (260), passenger—10.2 (260)
Recliner Angle Range, deg.	Driver—up to 88, passenger—(76 fold flat/88 non-fold flat)
SAE Front Volume Index, cu. ft. (cu. m.)	52.4 (1.485)
Rear Seat Head Room	38.9 (989.3)
Leg Room	35.6 (905.1)
Knee Clearance	0.9 (21.8)
Shoulder Room	53.4 (1357.2)
Hip Room	49.6 (1260.8)
SAE Rear Seat Volume Index, cu. ft. (cu. m.)	42.8 (1.212)
SAE Interior Volume, cu. ft. (cu. m.)	95.2 (2.697)
Cargo Volume Indexes	
Rear Seats Up, cu. ft. (cu. m)	18.5 (0.525)
Rear Seats Folded, cu. ft. (cu. m)	48.0 (1.36)
EPA Interior Volume Index, cu. ft. (cu. m)	113.9 (3.225)
Liftover Height	27.6 (701.4)

BODY

Layout _____ Transverse front-engine front-wheel drive
Construction _____ Unitized steel body

SUSPENSION

Front _____ Independent MacPherson strut, coil spring over gas-charged
shock absorbers and stabilizer bar
Rear _____ Multi-link-link independent with coil springs, link-type stabilizer bar,
gas-charged shock absorbers

STEERING

Type _____ Rack and pinion with hydraulic power assist
Overall Ratio _____ 16.6:1
Turning Diameter (curb-to-curb) _____ 39.6 ft. (12 m)
Steering Turns (lock-to-lock) _____ 2.76

TIRES

Size and Type _____ P225/45R19 Performance
Mfr. and Model _____ Goodyear
Revs per Mile (km) _____ 770 (479)

WHEELS

Type and Material _____ Cast Aluminum
Size 19 x 7.5

BRAKES

Front
Size and Type _____ 13.4 x 1.10 (340 x 28) vented disc with 1.65 (42)
dual-piston floating caliper
Swept Area _____ 303.5 sq. in. (1958 sq. cm)
Rear
Size and Type _____ 11.9 x 1.39 (302 x 10) solid disc with 1.4 (35)
single-piston floating caliper
Swept Area _____ 191.9 sq. in. (1238.3 sq. cm)
Power Assist Type _____ 10 (254) single-diaphragm vacuum
Four-wheel Anti-lock _____ Std.
Electronic Stability Program _____ Std.