

2009 DODGE RAM 1500 SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in inches (millimeters) unless otherwise noted. All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Body Styles _____ Regular Cab, Quad Cab[®] and Crew Cab

Assembly Plants:

Regular Cab _____ St. Louis, Missouri

Quad Cab[®] _____ Dodge City (Warren, MI)

Crew Cab _____ Dodge City (Warren, MI), St. Louis, Missouri

EPA Vehicle Class _____ Standard Pickup

Introduction Date _____ August 2008

ENGINE: 3.7-LITER V-6

Availability _____ Standard – 2WD Regular Cab or 2WD Quad Cab[®]

Type and Description _____ 90 degree V-6, liquid cooled with balance shaft

Displacement _____ 226 cu in (3701 cu cm)

Bore x Stroke _____ 3.66 x 3.57 (93.0 x 90.8)

Valve System _____ Chain-driven SOHC, 12 valves, Normally Open check-valve Lash Adjusters

Fuel Injection _____ Sequential, multi-port, electronic, returnless

Construction _____ Cast iron block and bedplate, aluminum alloy heads, balance shaft

Compression Ratio _____ 9.7:1

Power (SAE net) _____ 210 bhp (156 kW) @ 5200 rpm

Torque (SAE net) _____ 235 lb-ft (319 Nm) @ 4000 rpm

Max. Engine Speed _____ 6000 rpm (electronically limited)

Fuel Requirement _____ Unleaded regular, 87 octane (R + M)/2

Oil Capacity _____ 5.0 qt (4.7 L)

Coolant Capacity _____ 11.3 qt (10.71 L)

Emission Controls _____ 3-way catalytic converter and internal engine features¹

Estimated EPA Fuel Economy (MPG City/Hwy) _____ 14/20

¹ Meets Tier 1 requirements in all 50 states.

ENGINE: 4.7-LITER V-8

Availability _____ Standard – all 4WD and Crew Cab
 Type and Description _____ 90 degree V-8, liquid cooled
 Displacement _____ 287 cu in (4701 cu cm)
 Bore x Stroke _____ 3.66 x 3.40 (93.0 x 86.5)
 Valve System _____ Chain-driven SOHC, 16 valves, Normally Open check-valve Lash Adjusters
 Fuel Injection _____ Sequential, multi-port, electronic, returnless
 Construction _____ Cast iron block and bedplate, aluminum alloy heads
 Compression Ratio _____ 9.8:1
 Power (SAE net) _____ 310 bhp (231 kW) @ 5650 rpm
 Torque (SAE net) _____ 330 lb-ft (447 Nm) @ 3950 rpm
 Max. Engine Speed _____ 6000 rpm (electronically limited)
 Fuel Requirement _____ Unleaded regular, 87 octane (R + M)/2
 Oil Capacity _____ 6.0 qt (5.7 L)
 Coolant Capacity _____ 10.8 qt (10.23 L)
 Emission Controls:
 Federal _____ 3-Way catalytic converter and internal engine features²
 ULEV _____ Three 3-Way catalytic converters and internal engine features³
 Estimated EPA Fuel Economy (MPG City/Hwy):
 Two-Wheel Drive _____ 14/19
 Four-Wheel Drive _____ 13/18

² Meets Federal Tier 1 emission requirements in all states except California and Massachusetts.

³ Meets California ULEV Ultra-Low Emission Vehicle requirements in California and Massachusetts.

ENGINE: 5.7-LITER HEMI® V-8

Availability _____ Optional
 Type and Description _____ 90 degree V-8, liquid cooled
 Displacement _____ 345 cu in (5654 cu cm)
 Bore x Stroke _____ 3.92 x 3.58 (99.5 x 90.9)
 Valve System ___ Variable Cam Timing, Pushrod-operated overhead 16 valves, hydraulic lifters with roller followers
 Fuel Injection _____ Sequential, multi-port, electronic, returnless
 Construction _____ Deep-skirt cast iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
 Compression Ratio _____ 10.5:1
 Power (SAE net) _____ 390 bhp (291 kW) @ 5600 rpm
 Torque (SAE net) _____ 407 lb-ft (552 Nm) @ 4000 rpm
 Max. Engine Speed _____ 5800 rpm
 Fuel Requirement _____ Unleaded mid-grade, 89 octane (R+M)/2 – recommended, Unleaded regular, 87 octane (R+M)/2 – acceptable
 Oil Capacity _____ 7.0 qt (6.6 L)
 Coolant Capacity _____ 14.0 qt (13.33 L)
 Emission Controls _____ 3-way catalytic converter and internal engine features⁴
 Estimated EPA Fuel Economy (MPG City/Hwy) _____ 14/20 (2WD) 13/18 (4WD)

⁴ Meets Tier 1 requirements in all 50 states.

TRANSMISSION: 545RFE – AUTOMATIC, 5-SPEED OVERDRIVE

Availability _____ Standard – with 4.7L & 5.7L engines

Description _____ Full electronic control; Three planetary gear sets, one overrunning clutch, & electronically controlled converter clutch

Gear Ratios:

1st	_____	3.00
2nd	_____	1.67 – upshift; 1.50 kick-down
3rd	_____	1.00
4th	_____	0.75
5th	_____	0.67
Reverse	_____	3.00
Overall Top Gear with 3.21 axle	_____	2.15
Overall Top Gear with 3.55 axle	_____	2.38
Overall Top Gear with 3.92 axle	_____	2.63
Overall Top Gear with 4.10 axle	_____	2.75

TRANSMISSION: 42RLE – AUTOMATIC, 4-SPEED OVERDRIVE

Availability _____ Standard – with 3.7L engines

Description _____ Hydraulic control; Electronically controlled governor, overdrive lock out, and converter clutch

Gear Ratios:

1st	_____	2.84
2nd	_____	1.57
3rd	_____	1.00
4th	_____	0.69
Reverse	_____	2.21
Overall Top Gear with 3.55 axle	_____	2.45
Overall Top Gear with 3.92 axle	_____	2.70

TRANSFER CASE: NVG243

Availability _____ Standard
 Type _____ Part Time
 Shift Mechanism _____ Electronic
 Available Speeds _____ 2 Speed
 Low Range Ratio _____ 2.72
 Center Differential _____ None

Operating Modes:

- 2WD High
- 4WD High, Locked
- Neutral
- 4WD Low, Locked

TRANSFER CASE: NVG246

Availability _____ Optional
 Type _____ On Demand
 Shift Mechanism _____ Electronic
 Available Speeds _____ 2 Speed
 Low Range Ratio _____ 2.72
 Center Differential _____ None

Operating Modes:

- 2WD High
- Auto 4WD
- 4WD High, Locked
- Neutral
- 4WD Low, Locked

ELECTRICAL SYSTEM

Alternator _____ 160 Amp
Battery _____ (H7), low maintenance, 80 amp-hours, 625 CCA

BRAKES

Front:

Size _____ 13.2" x 1.1" (336 mm x 28 mm)
Type _____ Vented disc with 2.13" (54 mm) two-piston pin-slider caliper
Swept Area _____ 292 sq in (1884 sq cm)

Rear:

Size _____ 13.8" x 0.87" (352 mm x 22 mm)
Type _____ Solid disc with 2.13" (54 mm) single-piston pin-slider caliper
Swept Area _____ 274 sq in (1768 sq cm)
Power Assist Type _____ Dual-rate, tandem diaphragm vacuum

DIMENSIONS AND CAPACITIES

REGULAR CAB PICKUP

Model – Tire Size	2WD – 265/70R17		4WD – 265/70R17	
Box Length	Short	Long	Short	Long
Wheelbase – in (mm)	120.5 (3061.2)	140.5 (3569.2)	120.6 (3062.5)	140.5 (3570.5)
Track, Front – in (mm)	68.0 (1728.2)	68.0 (1728.2)	68.2 (1732.3)	68.2 (1732.3)
Track, Rear – in (mm)	67.5 (1714.9)	67.5 (1714.9)	67.5 (1714.7)	67.5 (1714.7)
Overall Length – in (mm)	209.0 (5308.5)	231.0 (5866.5)	209.0 (5308.5)	231.0 (5866.5)
Overall Width – in (mm)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)	79.4 (2017.4)
Overall Height – in (mm)	74.6 (1894.2)	74.4 (1889.2)	75.2 (1910.4)	75.0 (1906.2)
Ground Clearance:				
- Front Axle – in (mm)	9.7 (245.5)	9.6 (245.1)	9.0 (227.9)	9.0 (228.0)
- Rear Axle – in (mm)	9.0 (227.6)	9.0 (227.5)	8.6 (217.3)	8.6 (217.5)
Open Tailgate to Ground – in (mm)	34.8 (883.4)	34.6 (878.3)	35.0 (889.6)	34.9 (885.3)
Pickup Body Height – in (mm)	20.1 (511.1)	20.2 (513.0)	20.1 (511.1)	20.2 (513.0)
Approach Angle, degrees	18.8°	18.8°	20.5°	20.5°
Departure Angle, degrees	25.2°	24.1°	25.6°	24.4°
Ramp Breakover Angle, degrees	23.2°	21.4°	18.7°	16.6°
Frontal Area (sq. ft.)	TBD	35.8	TBD	TBD
Drag Coefficient (Cd)	TBD	0.384	TBD	TBD
Fuel Tank Capacity	26 gal standard	32 gal standard	26 gal standard	32 gal standard

QUAD CAB® PICKUP

Model	2WD – 265/70R17	4WD – 265/70R17
Wheelbase – in (mm)	140.5 (3569.2)	140.5 (3570.5)
Track, Front – in (mm)	68 (1728.2)	68.2 (1732.3)
Track, Rear – in (mm)	67.5 (1714.9)	67.5 (1714.7)
Overall Length – in (mm)	229 (5816.5)	229 (5816.5)
Overall Width – in (mm)	79.4 (2017.4)	79.4 (2017.4)
Overall Height – in (mm)	75.1 (1906.3)	75.7 (1922.3)
Ground Clearance:		
- Front Axle – in (mm)	9.6 (245.1)	9.0 (228.0)
- Rear Axle – in (mm)	9.0 (227.5)	8.6 (217.5)
Open Tailgate to Ground – in (mm)	34.6 (878.3)	34.9 (885.3)
Pickup Body Height – in (mm)	20.1 (511.1)	20.1 (511.1)
Approach Angle, degrees	18.8°	20.5°
Departure Angle, degrees	24.1°	25.4°
Ramp Breakover Angle, degrees	21.4°	16.6°
Frontal Area (sq. ft.)	TBD	36.6
Drag Coefficient (Cd)	TBD	0.432
Fuel Tank Capacity	26 gallon standard 32 gallon optional	26 gallon standard 32 gallon optional

CREW CAB PICKUP

Model	2WD – 265/70R17	4WD – 265/70R17
Wheelbase – in (mm)	140.5 (3569.2)	140.5 (3570.5)
Track, Front – in (mm)	68.0 (1728.2)	68.2 (1732.3)
Track, Rear – in (mm)	67.5 (1714.9)	67.5 (1714.7)
Overall Length – in (mm)	229.0 (5816.6)	229.0 (5816.6)
Overall Width – in (mm)	79.4 (2017.4)	79.4 (2017.4)
Overall Height – in (mm)	75.1 (1907.1)	75.7 (1923.0)
Ground Clearance:		
- Front Axle – in (mm)	9.6 (245.1)	9.0 (228.0)
- Rear Axle – in (mm)	9.0 (227.5)	8.6 (217.5)
Open Tailgate to Ground – in (mm)	34.6 (878.3)	34.9 (885.3)
Pickup Body Height – in (mm)	20.0 (508.6)	20.0 (508.6)
Approach Angle, degrees	18.8°	20.5°
Departure Angle, degrees	24.1°	25.4°
Ramp Breakover Angle, degrees	21.4°	16.6°
Frontal Area (sq. ft.)	TBD	36.6
Drag Coefficient (Cd)	TBD	0.420
Fuel Tank Capacity	26 gallon standard 32 gallon optional	26 gallon standard 32 gallon optional

CARGO BOX

Nominal Box Size	5 ft 7 in RAMBOX (Crew)	5 ft 7 in (Crew)	6 ft 4 in (Reg or Quad®)	8 ft (Reg)
SAE Volume - cu ft (cu m)	38.7 (1.1) Box Only 7.4 (0.2) R + L Side 46.1 (1.3) Total Volume	50.3 (1.4)	57.5 (1.6)	74.7 (2.1)
Length at Floor, Tailgate Closed – in (mm)	67.4 (1341.0)	67.4 (1712.4)	76.3 (1938.5)	98.3 (2496.5)
Cargo Width – in (mm)	51.1 (1297.6)	66.4 (1686.9)	66.4 (1686.9)	66.4 (1686.9)
Distance Between Wheelhouses – in (mm)	50.0 (1271.0)	51.0 (1295.4)	51.0 (1295.4)	51.0 (1295.4)
Depth – in (mm)	20.0 (508.6)	20.0 (508.6)	20.1 (511.1)	20.2 (513.0)
Tailgate Opening Width – in (mm)	50.6 (1285.0)	60.4 (1535.3)	60.4 (1535.3)	60.4 (1535.3)

ACCOMMODATIONS

Model	Regular Cab	Quad Cab[®]	Crew Cab
Seating Capacity, F/R	2 or 3 / n/a	2 or 3 / 3	2 or 3 / 3
Front			
- Head Room – in (mm)	40.3 (1022.6)	41.0 (1045.5)	41.0 (1040.5)
- Leg Room – in (mm)	41.0 (1041.3)	41.0 (1041.3)	41.0 (1041.4)
- Shoulder Room – in (mm)	66.0 (1676.4)	66.0 (1676.5)	66.0 (1676.5)
- Hip Room – in (mm)	62.9 (1676.4)	63.2 (1604.5)	63.2 (1604.5)
- Seat Travel – in (mm)	7.1 (179.2)	7.1 (179.2)	7.1 (179.2)
- Recliner Range (deg)	14.0°	42.0°	42.0°
Rear			
- Head Room – in (mm)	N/A	39.7 (1007.2)	39.9 (1013.5)
- Leg Room – in (mm)	N/A	36.8 (934.9)	42.0 (1067.9)
- Shoulder Room – in (mm)	N/A	65.7 (1669.9)	65.7 (1670.0)
- Hip Room – in (mm)	N/A	62.9 (1598.3)	63.2 (1605.2)
Interior Volume			
- Front – cu ft (cu m)	63.0 (1.8)	64.1 (1.8)	64.2 (1.82)
- Rear – cu ft (cu m)	N/A	55.5 (1.6)	63.7 (1.8)

BODY/CHASSIS

Model	2WD	4WD
Layout	Longitudinal, front engine	Longitudinal, front engine, transfer case
Construction	Ladder-type frame, steel cab, double-wall steel pickup box	Ladder-type frame, steel cab, double-wall steel pickup box

SUSPENSION

Model	2WD	4WD
Front	Upper and lower "A" arms, coil springs, twin tube shock absorbers, stabilizer bar	Upper and aluminum lower "A" arms, coil over twin tube shock absorbers, stabilizer bar
Rear	5-link with track bar, coil springs, stabilizer bar, twin tube shock absorbers, solid axle	5-link with track bar, coil springs, stabilizer bar, twin tube shock absorbers, solid axle

STEERING**REGULAR CAB PICKUP**

Model	2WD		4WD	
Box Length	Short Box	Long Box	Short Box	Long Box
Wheel Base	120.5" (3061 mm)	140.5" (3569 mm)	120.5" (3062 mm)	140.5" (3570 mm)
Overall Steering Ratio	19.1:1	17.89:1	19.1:1	17.89:1
Steering Wheel Turns (Lock-to-Lock)	3.5	3.3	3.5	3.3
Turning Diameter - 17" P265 Tire	39.5' (12.0 m)	45.1' (13.7 m)	39.8' (12.1 m)	45.4' (13.8m)
Turning Diameter - 20" P275 Tire	39.3' (12.0 m)	44.9' (13.7 m)	39.8' (12.1 m)	45.5' (13.9 m)
Turning Diameter - 17" LT275 Tire (TRX)	N/A	N/A	39.4' (12.0 m)	45.0' (13.7 m)

QUAD CAB® PICKUP

Model	2WD	4WD
Wheelbase	140.5" (3569 mm)	140.5" (3570 mm)
Overall Ratio	17.89:1	17.89:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter - 17" P265 Tire	45.1' (13.7 m)	45.4' (13.8 m)
Turning Diameter - 20" P275 Tire	44.9' (13.7 m)	45.5' (13.9 m)
Turning Diameter - 17" LT 275 Tire (TRX)	44.8' (13.7m)	45.0' (13.7 m)

CREW CAB PICKUP

Model	2WD	4WD
Wheelbase	140.5" (3569 mm)	140.5" (3570 mm)
Overall Ratio	17.89:1	17.89:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter - 17" P265 Tire	45.1' (13.7 m)	45.4' (13.8 m)
Turning Diameter - 20" P275 Tire	44.9' (13.7 m)	45.5' (13.9 m)
Turning Diameter - 17" LT275 Tire (TRX)	44.8' (13.7m)	45.0' (13.7 m)

MAXIMUM PAYLOAD CAPACITIES*

Standard Cab Short Box	Engine	Transmission	4WD / 2WD	GVW	Payload
	3.7L	Automatic	4X2	6025	1490
	4.7L	Automatic	4X2	6025	1290
	4.7L	Automatic	4X4	6350	1380
	5.7L	Automatic	4X2	6200	1470
	5.7L	Automatic	4X4	6350	1390
Standard Cab Long Box	Engine	Transmission	4WD / 2WD	GVW	Payload
	3.7L	Automatic	4X2	6600	1850
	4.7L	Automatic	4X2	6600	1750
	4.7L	Automatic	4X4	6600	1470
	5.7L	Automatic	4X2	6600	1690
	5.7L	Automatic	4X4	6600	1440
Quad Cab® Short Box	Engine	Transmission	4WD / 2WD	GVW	Payload
	3.7L	Automatic	4X2	6700	1790
	4.7L	Automatic	4X2	6700	1710
	4.7L	Automatic	4X4	6700	1430
	5.7L	Automatic	4X2	6700	1630
	5.7L	Automatic	4X4	6700	1390
Crew Cab Short Box	Engine	Transmission	4WD / 2WD	GVW	Payload
	4.7L	Automatic	4X2	6800	1650
	4.7L	Automatic	4X4	6800	1410
	5.7L	Automatic	4X2	6800	1640
	5.7L	Automatic	4X4	6800	1360

* Maximum values shown, payload will vary depending on vehicle trim level and option content.

ESTIMATED TRAILER TOW CAPACITIES*

3.7L Regular Cab – Short Box (1L61) - ST
3.7L Regular Cab – Long Box (1L62) - ST
3.7L Quad Cab® – Short Box (1L41) - ST

Engine	4WD 2WD	Trans	Axle	Tire	Trim	GCW	Quad Cab® Short Box Max Trailer	Reg Cab Short Box Max Trailer	Reg Cab Long Box Max Trailer
3.7L	4X2	Auto (4 Spd)	3.92	17" P265	ST	8,500	3,450	3,800	3,600
			3.55	17" P265	ST	8,500	N/A	3,800	N/A

*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo, and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

4.7L Regular Cab – Short Box (1L61, 1H61, 6L61, 6H61) – ST, SLT, TRX
4.7L Regular Cab – Long Box (1L62, 1H62, 6L62, 6H62) – ST, SLT, TRX

Engine	4WD 2WD	Trans	Axle	Tire	Trim	GCW	Reg Cab Short Box Max Trailer	Reg Cab Long Box Max Trailer
4.7L	4X2	Auto (5 Spd)	3.92	17" P265 17" LT275	ST, SLT, TRX	12,500	7,600	7,450
			3.92	20" P275	SLT	11,500	6,500	6,350
			3.55	17" P265 17" LT275	ST, SLT, TRX	11,500	6,600	6,450
			3.55	20" P275	SLT	10,500	5,500	5,350
	4X4	Auto (5 Spd)	3.92	17" P265 17" LT275	ST, SLT, TRX	12,500	7,400	7,200
			3.92	20" P275	SLT	11,500	6,300	6,100
			3.55	17" P265 17" LT275	ST, SLT, TRX	11,500	6,400	6,200
			3.55	20" P275	SLT	10,500	5,300	5,100

*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo, and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

ESTIMATED TRAILER TOW CAPACITIES* (CONT.)**4.7L Quad Cab® – Short Box (1L41, 1H41, 6L41, 6H41) – ST, SLT, TRX****4.7L Crew Cab – Short Box (1H98, 6H98) – SLT, TRX**

Engine	4WD 2WD	Trans	Axle	Tire	Trim	GCW	Reg Cab Short Box Max Trailer	Reg Cab Long Box Max Trailer
4.7L	4X2	Auto (5 Spd)	3.92	17" P265 17" LT275	ST, SLT, TRX	12,500	7,200	7,350
			3.92	20" P275	SLT	11,500	6,100	6,200
			3.55	17" P265	ST, SLT	11,500	6,200	6,350
			3.55	20" P275	SLT	10,500	5,100	5,200
	4X4	Auto (5 Spd)	3.92	17" P265 17" LT275	ST, SLT, TRX	12,500	6,950	7,100
			3.92	20" P275	SLT	11,500	5,950	5,950
			3.55	17" P265 17" LT275	ST, SLT, TRX	11,500	5,950	6,100
			3.55	20" P275	SLT	10,500	5,750	5,850

*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo, and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

5.7L Regular Cab – Short Box (1L61, 1H61, 6L61, 6H61) – ST, SLT, TRX, Sport (R/T)**5.7L Regular Cab – Long Box (1L62, 1H62, 6L62, 6H62) – ST, SLT, TRX**

Engine	4WD 2WD	Trans	Axle	Tire	Trim	GCW	Reg Cab Short Box Max Trailer	Reg Cab Long Box Max Trailer
5.7L	4X2	Auto (5 Spd)	4.10	20" P275	Sport (R/T)	10,000	5,000	N/A
			3.92	17" P265 17" LT275	ST, SLT, TRX	14,000	9,100	8,950
			3.92	20" P275	SLT	13,000	8,000	7,850
			3.55	17" P265 17" LT275	ST, SLT, TRX	13,000	8,100	7,950
			3.55	20" P275	SLT	12,000	7,000	6,850
			3.21	17" P265	ST, SLT	11,000	6,000	5,900
	4X4	Auto (5 Spd)	3.92	17" P265 17" LT275	ST, SLT, TRX	14,000	8,900	8,700
			3.92	20" P275	SLT, Sport	13,000	7,800	7,600
			3.55	17" P265 17" LT275	ST, SLT, TRX	13,000	7,900	7,700
			3.55	20" P275	SLT, Sport	12,000	6,800	6,600

*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo, and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

ESTIMATED TRAILER TOW CAPACITIES* (CONT.)

5.7L Quad Cab® – Short Box (1L41, 1H41, 1P41, 6L41, 6H41, 6P41) – ST, SLT, TRX, Sport, Big Horn, Lone Star, Laramie

5.7L Crew Cab – Short Box (1H98, 1P98, 6H98, 6P98) – SLT, TRX, Sport, Big Horn, Lone Star, Laramie

Engine	4WD 2WD	Trans	Axle	Tire	Trim	GCW	Crew Cab Short Box Max Trailer	Quad Cab® Short Box Max Trailer
5.7L	4X2	Auto (5 Spd)	3.92	17" P265 17" LT275	ST, SLT, TRX	14,000	8,700	8,800
			3.92	20" P275	SLT, Sport, Big Horn, Lone Star, Laramie	13,000	7,600	7,650
			3.55	17" P265 17" LT275	ST, SLT, TRX,	13,000	7,700	7,800
			3.55	20" P275	SLT, Sport, Big Horn, Lone Star, Laramie	12,000	6,600	6,650
			3.21	17" P265	ST, SLT	11,000	6,700	6,800
	4X4	Auto (5 Spd)	3.92	17" P265 17" LT275	ST, SLT, TRX	14,000	8,400	8,550
			3.92	20" P275	SLT, Sport, Big Horn, Lone Star, Laramie	13,000	7,300	7,400
			3.55	17" P265 17" LT275	ST, SLT, TRX	13,000	7,400	7,550
			3.55	20" P275	SLT, Sport, Laramie	12,000	6,300	6,400

*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo, and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).