



Body Style: Two-door sport-utility vehicle
Layout: Longitudinal front engine, 4WD
Seat Layout: 2/2
EPA Vehicle Class: Multi-purpose vehicle
Assembly: Toledo Supplier Park, Toledo Ohio

2010 JEEP WRANGLER; THE BENCHMARK OFF-ROAD VEHICLE

With more than 68 years of legendary off-road capability, the 2010 Jeep Wrangler doesn't sacrifice anything inside the cabin, offering safety and convenience features, interior space, versatility and comfort.

Whether choosing a Wrangler Sport, Sahara or Rubicon® model, 2010 Jeep Wrangler customers will experience best-in-class off-road capability in a true open-air sport-utility vehicle.

The 2010 Jeep Wrangler adds even more refinement with a new and improved Sunrider® soft-top system, making it even easier to remove the top for that open-air experience on- or off-road.

The Sunrider soft top is redesigned with a new cable-top system that allows customers to easily open and close the top within minutes. The improved soft top now features a simplified removal system, eliminating the need to un-tuck and tuck the side rails when opening and closing the top.

All 2010 Jeep Wrangler models include a fuel-saver indicator. The fuel-saver indicator provides drivers with continuous feedback on fuel consumption. The fuel-saver indicator will display when driving in a fuel-efficient manner.

Other standard features include compass and outside temperature display, fog lamps, tow hooks and larger sliding sun visors with mirrors.

Jeep Sahara and Rubicon models now feature new optional two-tone leather seating. And the Wrangler Sport model now features a new full-length floor console. In addition, cloth seats replace standard vinyl seats.

2010 Jeep Wrangler models feature a 3.8-liter V-6 engine which generates 202 horsepower (151 kW) and 237 lb.-ft. (321 N•m) of torque, backed by a standard six-speed manual gearbox or an available four-speed automatic transmission.

2010 Jeep Wrangler Sport and Sahara models are equipped with the Command-Trac® NV241 part-time, two-speed transfer case with a 2.72:1 low-range gear ratio. An available Trac-Lok® limited-slip rear differential provides extra torque and grip during slippery, low-traction situations, such as driving over sand, gravel, snow or ice.

The 2010 Jeep Wrangler Rubicon model is equipped with an Off-Road Rock-Trac® NV241 two-speed transfer case with a 4.0:1 low-range gear ratio, as well as electric front- and rear-axle lockers, an electronic sway-bar disconnect and 32-inch off-road tires.

MODELS / POWERTRAINS

MODEL	ENGINE	TRANSMISSIONS	
	3.8L V-6	6-SPEED MANUAL OVERDRIVE (NSG 370)	4-SPEED AUTO OVERDRIVE (42RLE)
Sport	S	S	0
Sahara	S	S	0
Rubicon	S	S	0

NEW FOR 2010

- Improved Sunrider® soft top with easy-to-remove system
- Fuel-saver indicator standard on all models
- New Satin Silver 18-inch aluminum wheels standard on Sahara
- New Satin Carbon 17-inch aluminum wheels standard on Rubicon
- Fog lamps standard on all models
- Tow hooks standard on all models
- Standard full-length floor console replaces mini console on base two-door Wrangler Sport
- Uconnect™ Phone included with optional Uconnect Navigation
- Compass and outside temperature readout standard on all models
- Cloth seats replace standard vinyl seats on base two-door Wrangler Sport
- Larger, sliding sun visors with mirrors
- New front dome lamp with on/off switch
- New two-tone leather seating available on Sahara and Rubicon
- Surf Blue replaces Jeep Green Metallic Clear Coat exterior color
- Natural Green replaces Detonator Yellow exterior color
- Dark Charcoal replaces Sunburst Orange exterior color

SAFETY AND SECURITY


More than 25 safety and security features available including:

- Advanced Multi-stage Air Bags
- Anti-lock Brake System (ABS)
- Electronic Stability Control (ESC)
- Seat-mounted Side Air Bags
- Side-impact Door Beams

FUEL ECONOMY (city/hwy)

3.8L OHV V-6
 15/19 – 4WD

DIMENSIONS, IN. (MM)



O.A. Width: 73.7 (1872.9)

Track, Front: 61.9 (1572.3)

Track, Rear: 61.9 (1572.3)

^(a) Hard top

Curb Wt. lb.(kg):

3,760 (1403) –

4,129 (1541) (varies)

2010 JEEP® WRANGLER AT A GLANCE

The ultimate Jeep

- 69 years later, Jeep continues to offer legendary capability

Benchmark Jeep characteristics

- Off-road capability
 - Dana front and rear solid axles, available next-generation Command-Trac® and Rock-Trac® transfer cases and electric axle lockers
 - Electronic-disconnecting sway bar – Active Sway Bar System
 - Equipped with skid plates, tow hooks and available 32-inch BF Goodrich tires
- Power
 - A standard 3.8-liter V-6 engine with 202 horsepower (151 kW) and 237 lb.-ft. (321 N•m) of torque includes a standard six-speed manual transmission or four-speed automatic transmission
- Interior space and comfort
 - Front-seat area provides 54.6 cubic-feet of space for comfortable shoulder and hip room, while rear-seat space is 48.3 cubic-feet
 - Space behind the rear seat provides more comfort, ergonomics and storage capacity
 - 56.5 cu.-ft. of cargo volume behind front seats
 - 17.1 cu.-ft. of cargo volume behind rear seats
- On-road refinement
 - Torsionally stiff frame resists bending
 - Wheelbase at 95.4 inches, which contributes to a smooth ride and quiet cabin
 - Advanced shock tuning and heavy-duty powertrain and body mounts isolate passenger compartment from vibrations
- Open-air fun
 - Only true 4x4 convertible
 - Standard Sunrider® soft top provides options for open-air driving, while the Freedom Top® three-piece modular hard top provides a second, easy open-air option

- Safety features
 - Hill-start Assist (HSA)
 - Available Trailer-sway Control (TSC)
 - Advanced Multi-stage Air Bags
 - Anti-lock Brake System (ABS)
 - Brake Assist
 - LATCH (Lower Anchors and Tethers for Children)
 - Electronic-roll Mitigation (ERM)
 - Electronic Stability Control (ESC)
 - Energy-absorbing steering column
 - Seat-Belt Pretensioners
 - Seat-mounted Side Air Bags
 - Side-impact Door Beams
 - Tire-pressure Monitoring (TPM)

True to Jeep heritage

- Features classic round headlamps, signature seven-slot grille, wide wheel flares, exposed forged hinges, fold-down windshield, sport bar, removable tops and doors, and washable interior

Rugged Jeep character with new conveniences and features

- Available Uconnect™ Navigation with Uconnect Phone, six-disc stereo, MP3 player and SIRIUS Satellite Radio provide the latest interior conveniences
- Available power windows and door locks are designed so that doors may be easily removed

2010 JEEP® WRANGLER SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION

Body Style	Two-door sport-utility vehicle
Assembly Plant	Toledo, Ohio
EPA Vehicle Class	Multi-purpose vehicle

ENGINE: 3.8-LITER, OHV, 12-VALVE SMPI V-6

Availability	Standard
Type and Description	Six-cylinder, 60° V-type, liquid-cooled
Displacement	230.5 cu. in. (3778 cu. cm)
Bore x Stroke	3.78 x 3.43 (96 x 87)
Valve System	OHV, 12 valves, roller followers, hydraulic lifters
Fuel Injection	Sequential, multi-port, electronic
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	9.6:1
Power (SAE net)	202 hp (151 kW) @ 5,200 rpm (53.9 hp/L)
Torque (SAE net)	237 lb.-ft. (321 N•m) @ 4,000 rpm
Fuel Recommendation	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	6.0 qt. (5.7L) plus filter
Coolant Capacity	13.36 qt. (12.64L) std.
Emission Controls	Two mini-oxidation three-way catalytic converters, four heated oxygen sensors, electronic EGR and internal engine features. Meets Tier 2 Bin 5 (federal) and LEV 2 (CA) emission requirements

ELECTRICAL SYSTEM

Alternator	140-amp
Battery	600 CCA, maintenance-free

TRANSMISSION: NSG 370—MANUAL, SIX-SPEED OVERDRIVE

Availability	Standard on all models
Description	Synchronized in all forward gears and Reverse, multi-rail shift system with top-mounted shift lever
Clutch	Hydraulic actuation
Gear Ratios	
1st	4.46
2nd	2.61
3rd	1.72
4th	1.25
5th	1
6th	0.84
Reverse	4.06
Axle Ratio	3.21 standard, 4.10 optional (standard on Rubicon)
Overall Top-gear	2.69 standard, 3.44 optional (standard on Rubicon)

2010 JEEP® WRANGLER SPECIFICATIONS

TRANSMISSION: 42RLE—AUTOMATIC, FOUR-SPEED OVERDRIVE

Availability	Optional on all models
Description	Electronic governor, electronically controlled converter clutch
Gear Ratios	
1st	2.84
2nd	1.57
3rd	1
4th	0.69
Reverse	2.21
Axle Ratio	4.1
Overall Top-gear	2.83

TRANSFER CASE: NV241 COMMAND-TRAC®

Type	Part-time
Operating Modes	2WD High; 4WD High; Neutral; 4WD Low
Low-range Ratio	2.72:1
Center Differential Type	None

TRANSFER CASE: NV241OR ROCK-TRAC®

Type	Part-time, heavy-duty
Operating Modes	2WD High; 4WD High; Neutral; 4WD Low
Low-range Ratio	4.0:1
Center Differential Type	None

DIMENSIONS AND CAPACITIES

General Overall Length	152.8 (3881.2)
Overall Width (without Mirrors)	73.7 (1872.9)
Overall Height, Hard Top	70.9 (1800.1)
Wheelbase	95.4 (2424.1)
Track, Front	61.9 (1572.3)
Track, Rear	61.9 (1572.3)
Overhang, Front	26.7 (679.2)
Overhang, Rear	30.6 (777.9)
Maximum Payload (includes Occupants and Cargo)	1,000 lbs. (454 kg)
Fuel-tank Capacity	18.6 gallons

CLEARANCES

	P225/75R16	P245/75R16	P255/75R17	P255/70R18	LT255/75R17
Approach Angle, Deg.	40.8	42.0	43.8	44.6	44.3
Breakover Angle, Deg.	21.8	23.1	24.9	25.5	25.4
Departure Angle, Deg.	37.4	38.7	40.3	40.6	40.4
Front Axle to Ground (inches)	9.1	9.6	10.3	10.6	10.5
Rear Axle to Ground (inches)	8.8	9.4	10.1	10.3	10.2

2010 JEEP® WRANGLER SPECIFICATIONS

CURB WEIGHT

Wrangler Sport, Manual Transmission	3,760 lbs. (1403 kg)
Wrangler Sport, Automatic Transmission	3,785 lbs. (1413 kg)
Wrangler Sahara, Manual Transmission	3,951 lbs. (1475 kg)
Wrangler Sahara, Automatic Transmission	3,976 lbs. (1484 kg)
Wrangler Rubicon, Manual Transmission	4,104 lbs. (1532 kg)
Wrangler Rubicon, Automatic Transmission	4,129 lbs. (1541 kg)

ACCOMMODATIONS

Seating Capacity, F/R	2/2
Front	
Head Room	41.3 (1048.4)
Leg Room	41.0 (1041.4)
Shoulder Room	55.8 (1416.7)
Hip Room	55.6 (1412.8)
Seat Travel	Driver—9.4 (239.5), Passenger—9.4 (239.5)
Front-Volume Index, cubic ft. (cu. m)	54.6 (1.55)
Rear	
Head Room	40.3 (1024.6)
Leg Room	35.6 (904.2)
Shoulder Room	61.6 (1565.9)
Hip Room	44.7 (1135.6)
Rear-Seat Volume Index, cubic ft. (cu. m)	48.3 (1.367)
Cargo Liftover Height	27.8 (706.1)
Maximum Cargo Width at Swing-Gate Opening	58.7 (1491.0)
Minimum Cargo Width at Swing-Gate Opening	41.2 (1046.5)
Maximum Cargo Height at Swing-Gate Opening	37.1 (942.3)
Minimum Cargo Height at Swing-Gate Opening	37.0 (939.8)
Distance Between Wheelhouses	44.7 (1135.4)
Cargo Volume cubic ft. (cu. m)	
Rear Seat Installed	56.5 cu. ft. (1.60)
Rear Seat Removed	61.2 cu. ft. (1.73)
Behind Rear Seat	17.15 cu. ft. (0.19)

BODY AND CHASSIS

Layout	Longitudinal front engine, four-wheel drive
Construction	Ladder-type frame, open steel body

SUSPENSION

Front	Live axle, leading arms, track bar, coil springs, stabilizer bar, low-pressure (on 16-inch wheel packages) gas-charged shock absorbers— Standard Monotube high-pressure (on 17- and 18-inch wheel packages) gas-charged shock absorbers—Standard; Electronic Sway-Bar Disconnect System—Standard, Rubicon
Rear	Live axle, trailing arms, track bar, coil springs, stabilizer bar, low-pressure (on 16-inch wheel packages) gas-charged shock absorbers— Standard Monotube high-pressure (on 17- and 18-inch wheel packages) gas-charged shock absorbers—Standard

2010 JEEP® WRANGLER SPECIFICATIONS

STEERING

Type	Power, recirculating ball with damper
Overall Ratio	16.7:1 overall
Turning Diameter (curb-to-curb)	34.9 ft. (10.62 m)
Steering Turns (lock-to-lock)	3.5

BRAKES

Availability	Standard on all models
Power-assist Type	10 (254) single-diaphragm vacuum
Four-wheel Anti-lock Brake System (ABS) with On- and Off-road Calibrations	Standard
Electronic Stability Control (ESC)	Standard
Parking Brake Type	Drum-in-hat
Front Size and Type	11.9 x 1.1 (302 x 28) vented rotor with 2.6 (66) single-piston floating caliper
Swept Area (Total Front)	234.3 inches
Rear Size and Type	12.44 x 0.47 (316 x 12) solid rotor with 1.9 (48) single-piston floating caliper
Swept Area (Total Rear)	202.6 inches

WHEELS

Availability	Standard on Wrangler Sport
Type and Material	Painted steel
Size	16 x 7.0

Availability	Standard on Wrangler Sahara
Type and Material	Painted cast-aluminum
Size	18 x 7.5

Availability	Standard on Wrangler Rubicon
Type and Material	Painted cast-aluminum
Size	17 x 7.5

TIRES

Availability	Standard on Wrangler Sport
Size and Type	P225/75R16, on/off-road, black sidewall
Mfr. and Model	Goodyear Wrangler ST
Revs per Mile (km)	712 (1146)

Availability	Standard on Wrangler Sahara
Size and Type	P255/70R18, on/off-road, OWL
Mfr. and Model	Bridgestone Dueler 693
Revs per Mile (km)	653 (1051)

Availability	Standard on Wrangler Rubicon
Size and Type	LT255/75R17, on/off-road, black sidewall
Mfr. and Model	BF Goodrich Mud Terrain
Revs per Mile (km)	650 (1046)

2010 JEEP® WRANGLER SPECIFICATIONS

TOWING CAPACITIES

WRANGLER TWO-DOOR SPORT 4WD-LHD

Engine	Trans. Type	Transmission	Axle Ratio	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail
3.8L V-6 gas (EGT)	M6	NSG370 6-SPD MANUAL (DEH)	3.21 **	1000	3839	1945	1893	2775	3000	4910	1000
3.8L V-6 gas (EGT)	M6	NSG370 6-SPD MANUAL (DEH)	3.73	1000	3839	1945	1893	2775	3000	5910	2000
3.8L V-6 gas (EGT)	A4	42RLE VLP 4-SPD AUTO (DGV)	3.73	1000	3963	1951	1912	2775	3000	5935	2000

¹ GCWR = Base Weight + Maximum Trailer Weight + 150 lbs. for driver.

² ** AHT Trailer-tow Package not available with 3.21 axle ratio.

WRANGLER TWO-DOOR SAHARA 4WD-LHD

Engine	Trans. Type	Transmission	Axle Ratio	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail
3.8L V-6 gas (EGT)	M6	NSG370 6-SPD MANUAL (DEH)	3.21 **	880	4005	2009	1996	2775	3200	5155	1000
3.8L V-6 gas (EGT)	M6	NSG370 6-SPD MANUAL (DEH)	3.73	880	4005	2009	1996	2775	3200	6155	2000
3.8L V-6 gas (EGT)	A4	42RLE VLP 4-SPD AUTO (DGL)	3.73	880	4029	2015	2015	2775	3200	6179	2000

¹ GCWR = Base Weight + Maximum Trailer Weight + 150 lbs. for driver.

² ** AHT Trailer-tow Package not available with 3.21 axle ratio.

WRANGLER TWO-DOOR SPORT 4WD-RHD

Engine	Trans. Type	Transmission	Axle Ratio	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail
3.8L V-6 gas (EGT)	A4	42RLE VLP 4-SPD AUTO (DGV)	3.73	740	3972	1986	1986	2775	3000	6122	2000

¹ GCWR = Base Weight + Maximum Trailer Weight + 150 lbs. for driver.

² ** AHT Trailer-tow Package not available with 3.21 axle ratio.

WRANGLER TWO-DOOR RUBICON 4WD-LHD

Engine	Trans. Type	Transmission	Axle Ratio	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail
3.8L V-6 gas (EGT)	M6	NSG370 6-SPD MANUAL (DEH)	4.10	892	4082	2058	2024	2775	3200	6232	2000
3.8L V-6 gas (EGT)	A4	42RLE VLP 4-SPD AUTO (DGV)	4.10	892	4107	2064	2043	2775	3200	6257	2000

¹ GCWR = Base Weight + Maximum Trailer Weight + 150 lbs. for driver.

² ** AHT Trailer-tow Package not available with 3.21 axle ratio.

2010 JEEP® WRANGLER FEATURE AVAILABILITY

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication and is subject to change.

	Sport	Sahara	Rubicon
EXTERIOR			
Colors			
Natural Green Pearl Coat			
Deep Water Blue Pearl Coat			
Brilliant Black Crystal Pearl Coat			
Bright Silver Metallic Clear Coat			
Dark Charcoal Pearl Coat			
Red Rock Crystal Pearl Coat	O	O	O
Flame Red Clear Coat			
Surf Blue Pearl Coat			
Stone White Clear Coat	O	—	O
Doors			
Two doors, removable	S	S	S
Full, metal with roll-up windows (included with hard or dual top)	S	S	S
Half, metal (not available with hard or dual-top options)	O	—	O
Fender Flares			
Black	S	—	S
Body-color	—	S	—
Fog Lamps			
	S	S	S
Grille—Body-color			
	S	S	S
Halogen Headlamps			
	S	S	S
Mirrors—Dual, swing-away, manual, Black			
	S	S	S
Rock rails—Heavy-duty, black-painted steel			
	—	—	S
Side Steps—Tubular			
	O	S	—
Tops			
Sunrider® soft top with “sun roof” feature	S	S	S
Freedom Top®- Three-piece modular hardtop	O	O	O
Tow Hooks—Two, front; one, rear			
	S	S	S
Windshield—Fold-down, sunscreen			
	S	S	S
Windshield wipers—Two-speed with variable intermittent mode			
	S	S	S
INTERIOR			
Assist Handle—Passenger			
	S	S	S
Carpeting			
Front seat, rear seat, wheelhouse and cargo area	S	S	S
Cargo Tie-down Loops—two			
	S	S	S
Climate Control			
Air conditioning	O	S	S
Console—Floor			
Full-length with front and rear cup holders, locking storage bin	S	S	S
Door Locks—Power			
	P	S	P
Floor Mats—Carpeted, front			
	S	S	S
Glove Compartment			
	S	S	S

2010 JEEP® WRANGLER FEATURE AVAILABILITY

	Sport	Sahara	Rubicon
Instrument Cluster			
Gauges—Speedometer, tachometer, odometer, trip odometer, temperature, fuel level, oil pressure, voltmeter	S	S	S
Temperature and compass gauge	S	S	S
Mirrors			
Manual day/night rearview	S	S	S
Power Accessory—12-volt power outlet in instrument panel	S	S	S
Radios			
AM/FM stereo radio with CD player and MP3/WMA auxiliary input jack	S	S	S
AM/FM stereo radio with six-disc DVD/CD changer and MP3/WMA auxiliary input jack	0	0	0
Uconnect Navigation and Phone	—	0	0
SIRIUS Satellite Radio	0	S	S
Six speakers	S	S	S
Six Infinity speakers and subwoofer with 368-watt high power amplifier	0	S	S
Seat Fabric			
Cloth	S	S	S
Two-Tone Leather	—	0	0
Seats, Front			
Reclining bucket with adjustable head restraints	S	S	S
Seats, Rear			
Fold-and-tumble bench (removable)	S	S	S
Speed Control			
	P	S	S
Sport Bar—With full padding, two speakers and switchtable dome light	S	S	S
Steering Column—Tilt, manual	S	S	S
Steering Wheel			
Leather-wrapped with speed control	P	S	S
Storage—Secured, under rear cargo area floor	S	S	S
Sun Visors—Driver and front-passenger, sliding with mirrors	S	S	S
Windows—Power	P	S	P

POWERTRAIN AND CHASSIS

Alternator—140-amp	S	S	S
Battery—600-amp maintenance-free	S	S	S
Brakes			
Four-wheel disc brakes with vented front, solid rear discs, and Anti-lock Brake System (ABS) with on- and off-road calibrations	S	S	S
Differential			
Trac-Lok® rear limited-slip	0	0	—
Tru-Lok® front and rear electronic remote locking	—	—	S
Engines			
3.8-liter OHV, 12-valve SMPI V-6 engine and six-speed NSG 370 manual transmission	S	S	S
3.8-liter OHV, 12-valve SMPI V-6 engine and four-speed 42RLE automatic transmission	0	0	0
Engine Block Heater	0	0	0
Front Axle			
Enhanced Dana 30	S	S	—
Dana 44, heavy-duty	—	—	S
Electronic Front-axle Locker	—	—	S

2010 JEEP® WRANGLER FEATURE AVAILABILITY

	Sport	Sahara	Rubicon
Rear Axle			
Dana 44, heavy-duty	S	S	S
3.21 axle ratio with manual	S	S	—
3.73 axle ratio with automatic, optional manual	O	O	—
4.10 axle ratio	—	—	S
Electronic Rear-axle Locker	—	—	S
Skid Plates —Fuel tank, transfer case, automatic transmission oil pan (w/ATX)	S	S	S
Steering —Power	S	S	S
Suspension			
Quadra-Coil	S	S	S
Front: five-link solid axle, gas-charged shock absorbers, stabilizer bar	S	S	S
Front: Electronic Sway-bar Disconnect System	—	—	S
Rear: five-link solid axle, gas-charged shock absorbers, stabilizer bar	S	S	S
Tire —Spare, swing-gate mounted, full-size with matching wheel	S	S	S
Tires			
Goodyear Wrangler ST P225/75R16 BWL, on/off-road	S	—	—
Goodyear Wrangler SRA P255/75R17 OWL, on/off-road	O	—	—
Bridgestone Dueler 693 P255/70R18 OWL, on/off-road	—	S	—
BF Goodrich Mud Terrain LT255/75R17 BWL, on/off-road	—	—	S
Transfer Case			
Command-Trac® part-time two-speed	S	S	—
Rock-Trac™ two-speed with 4.0:1 low-range gear ratio	—	—	S
Wheels			
16-inch x 7.0-inch painted steel	S	—	—
17-inch x 7.5-inch painted cast-aluminum	P	—	—
17-inch x 7.5-inch painted cast-aluminum	—	—	S
18-inch x 7.5-inch painted cast-aluminum	—	S	—

(a) Trac-Lok® is a registered trademark of Spicer Technology Inc.

SAFETY AND SECURITY

Brake Assist	S	S	S
Brake-Lock Differentials	S	S	S
Electronic-roll Mitigation (ERM)	S	S	S
Electronic Stability Control (ESC)	S	S	S
Hill-start Assist (HSA) (Manual Transmission)	S	S	S
Restraint Systems			
Air bags®, advanced multi-stage driver and front-passenger air bag	S	S	S
Occupant-classification System (OCS)	S	S	S
LATCH (Lower Anchors and Tethers for Children)	S	S	S
Front-seat-mounted side air bags	O	O	O
Remote keyless entry	P	S	P
Remote start (available with automatic transmission only)	—	O	O
Seat Belts			
Driver's-side Constant-force Retractors (CFR)	S	S	S
Front—Three-point belts with adjustable turning loops and traveling inboard buckles	S	S	S
Rear—Three-point belts	S	S	S

2010 JEEP® WRANGLER FEATURE AVAILABILITY

	Sport	Sahara	Rubicon
Seats—Rear, outboard head restraints	S	S	S
Sentry Key® engine immobilizer	S	S	S
Tire-pressure Monitoring (TPM)	S	S	S
Traction Control—All-speed	S	S	S
Warning Chime—Key-in-Ignition, headlamps-on, seat belt, check gauges	S	S	S

^(a) Certified to meet federal regulations that allow less forceful air bags. Always use seat belts.
Remember, a back seat is the safest place for children.

PACKAGES / EQUIPMENT GROUPS

Power Convenience Group—Includes power locks, one-touch down power windows, remote keyless entry (requires full metal doors) and security alarm	O	S	O
Premium Appearance Group—Includes silver front and rear bumper overlays as well as interior silver accents on HVAC outlet bezels and steering wheel spokes	—	S	—
Trailer-tow package—Includes 3.73 axle ratio (4.10 on Rubicon), receiver hitch and 4-pin connector — Now also includes Trailer-sway Control (TSC)	O	O	O
Removable ashtray and lighter element	O	O	O

Legend: S = Standard O = Optional P = Available within package or group — = Not available

NOTES

Handwriting practice lines for the notes section, consisting of multiple sets of dotted lines for tracing and solid lines for independent writing.